

## FEATURES:

- Input: AC 100-240V~ 50/60Hz
- Available plug: US, EU, US foldable plug
- Power: 45W PD Charger
- Ovp, Ocp, Scp and Over load protection
- GAN TECH, PD Charger, smart
- Efficiency level: VI
- Dimension: 46.5\*46\*28mm
- Application: Tablet, Mobile phone, etc...



## SAFETY:

SAFETY:	
Safety Standard	UL 62368, IEC 62368, EN 61558, IEC60601, IEC60335, IEC60065
Safety Approval	UL/cUL, CE, FCC, UKCA, PSE, CB, SAA, KC, TUV
EMC Standard	EMC EMISSION: EN55032 class B (CISPR32), EN61000-3-2, -3, EAC TP TC 020 EMC IMMUNITY: EN61000-4-2, 3, 4, 5, 6, 8, 11, EN55024; light industry level, criteria A, EAC TP TC 020
MTBF	50K hrs min. MIL-HDBK-217F (25°C)

## MODEL LIST:

MODEL	USB PORT	OUTPUT	Single Port POWER	TOTAL POWER
P245D-2C	USB C PORT 1	PD: 5V3, 9V3A, 12V3A, 15V3A, 20V2.25A PPS: 5-11V 4.05A	45W	45W
	USB C PORT 1	PD: 5V3, 9V3A, 12V3A, 15V3A, 20V2.25A PPS: 5-11V 4.05A	45W	
MODEL	USB PORT	OUTPUT	Single Port POWER	TOTAL POWER
P245D-2C	USB C PORT 1	PD: 5V3, 9V3A, 12V3A, 15V3A, 20V2.25A PPS: 5-11V 4.05A	45W	45W
	USBA PORT 1	5V3.0A.9V2.0A.12V1.5A	18W	
MODEL	USB PORT	OUTPUT	Single Port POWER	TOTAL POWER
P245D-1C	USB C PORT 1	PD: 5V3, 9V3A, 12V3A, 15V3A, 20V2.25A	45W	45W

## Mechanical Diagram:

STARWELL TECH CO LTD				版本	1.0
文件编号	制图	审核	批准	单位	mm
图纸名称	DK98T外观			比例	1:1
物料编号				日期	2022.10.20